
## **Mersen Whole Home Surge Protection**

Mersen's STLC surge protective device adds a critical layer of surge protection to the entire home. This simple whole house solution is installed directly in the electrical panel and has flexibility to fit in a variety of different load center manufacturers and models. The STLC Series satisfies the new 2020 NEC Article 230.67 requirement for surge protection for residential dwellings.

## Features:

- Designed with TPMOV Technology
- Quickly installs directly into load center bus bar, utilizing any (two) open adjacent breaker slots
- Fits into most residential load centers with 1" spacings
- 3-year manufacturer's warranty, plus up to \$25k connected equipment warranty





TECHNICAL DATA		
MARS Part No.	83937	
UL SPD Type	Type 1	
Nominal Discharge Current Rating (In)	10kA	
Surge Capacity (per phase and per mode)	25kA	
Short Circuit Current Rating (SCCR)	10kA (tested to 100kA)	
Maximum Continuous Operating Voltage (MCOV)	L-N: 150; L-L: 300	
Voltage Protection Rating (VPR)	L-N: 600; L-L 1000	
Ambient Temperature Rating	-20 - 65	
Applications	120/240 VAC residential load centers	
Approvals/Standards	UL1449 5th Edition, RoHS Compliant	
Led Status Indicator	On=Good, Off=Replace	
Response Time	Less than 1 nanosecond (one per phase)	

## **Compatability Chart**

BRAND	LOAD CENTER	CIRCUIT BREAKER TYPE
Eaton	BR Series (prefix 1BR or B in the catalog number)	BR215BR250, BR, 2P, 120/240 V AC, 15A50A
	PL Series (prefix P or PW in the catalog number)	Q215 Q250 , QP, 2P, 120/240VAC, 15A 50A
Siemens Industry, Inc	ES Series (prefix S or SW in the catalog number)	Q215 Q250 , QP, 2P, 120/240VAC, 15A 50A
	EQ Series (prefix E in the catalog number)	Q215 Q250 , QP, 2P, 120/240VAC, 15A 50A
Murray/Siemens Industry, Inc.	LC Series (prefix LC or LW in the catalog number)	MP215 MP250, MP, 2P, 120/240VAC, 15A 50A
ABB / General Electric	Powermark Gold series (prefix TL, TM or TP in the catalog number)	THQL215 THQL250, 2P, 120/240 V AC, 15 50 A
Schneider Electric USA Inc./Square D Co.	Homeline series (prefix HOM in the catalog number)	HOM215 HOM250, 2P, 120/ 240 V AC, 15 50 A



